

New *Corkstone*

The durability of linoleum combined with the warmth of natural cork makes Corkstone very unique. The technical characteristics of both materials combine to make a truly exceptional floor. The scope of application of the Corkstone line with its authentic stone appearance ranges from the kitchen to the bathroom to commercial applications. The lightly textured surface also allows for large areas to be virtually seamless.



FOSSIL



SLATE RIO NEGRO



GRANITE GARDA



MARINARO



TORRADO



Available in 12" x 36" planks

Technical Data

NovaCork™

General Information:

- Natural and Environmentally Friendly
- Thermal & Acoustic Insulating
- Durable
- Easy, Glueless Installation
- Hypoallergenic
- Antistatic

Composition:

- 2mm or 3mm Cork Surface Layer
- 6.8mm HDF Click Center Board
- 1.2mm Cork Underlayment

Sound Rating:

- 17DB

Fire Class Rated:

- Class B2

Thermal Insulation:

- RTD133

Specifications:

- 7/16" or 3/8" x 12" x 36"
- 6 or 7 Planks, 18.08 sq/ft or 21 sq/ft per carton
- Net Wt. 34 lbs. Per carton (Sold in full cartons only)

Warranty:

- 10 years Light Commercial Wear Warranty
- 20 years Residential Wear Warranty

(Please ask for a copy of Nova Distinctive Floors' warranty)

NOVA

Distinctive Floors™

1710 East Sepulveda Boulevard
Carson, California 90745

Tel: (866) 576.2458
Fax: (310) 830.9589
www.novafloorings.com



Nova Corkstone™

General Information:

- Very Durable
- Easy to maintain + keep hygienically clean
- Anti-static
- Anti-bacterial
- Can be used with radiant heat
- Pollutant-free

Composition:

- Top Layer - 2mm
- Middle HDF - 6.8mm
- Bottom Layer Cork - 1.2mm

Sound Rating:

- 20 DB

Fire Class Rate:

- EN-ISO 9239-1 / CFL s 1 (B 1)

Specifications:

- 3/8" x 12" x 36" (nominal)
- 6 planks, 18.08 sq/ft per carton
- Net Wt. 34 lbs
(Sold in full cartons only)

Warranty:

- 10 years Light Commercial Wear Warranty
- 20 years Residential Wear Warranty

(Please ask for a copy of Nova Distinctive Floors' warranty)

NovaCork Underlayment™

General Information:

Description: Sound deadening underlayment used under hardwood, ceramic tile, laminate floorings in commercial and residential applications.

Sizes: 6mm & 12mm sheets and 6mm rolls.

Floatation Tests: None after 3 hours immersion in boiling water.

Binder: Resin of polyurethane

Base: Composition of cork granules. Size 1-3

Density: 180-220 kg/cubic meter
(11.23-13.73 lbs/cubic foot)

Tensile Strength: 5-10 kg-sq/cm

Recovery (%): >= 75

Flexibility: F5 Pass

Thermal Conductivity: 0.0410 kcal/mh°c

Compression (%): 25-35

Dimensional: Length & Width: +/- 0.5mm

Thickness: +/- 0.2mm

Acoustical Rating: ASTM E 90-04; E 413-04, 492-04; E 986-04; E 986-06

6mm Thick	STC	IIC	ΔIIC
6" concrete slab Ceramic Finish	52	47	18
6" concrete slab Wood laminate	51	51	21

12mm Thick	STC	IIC	ΔIIC
6" concrete slab Ceramic Finish	54	49	19
6" concrete slab Wood Laminate	51	51	22